

Technical Data


CM12-8P-5MPU

M12 female 0° A-cod. with cable

PUR 8x0.25 bk 5m


SEN
NBK **SOR**

Made in Italy



1	↷	white
2	↷	brown
3	↷	green
4	↷	yellow
5	↷	gray
6	↷	pink
7	↷	blue
8	↷	red

Female



Technical Data

CM12-8P-5MPU

Standard:	IEC 61076-2-101
Rated Voltage:	30 V
Rated Current:	2 A
Insulation:	≥100MΩ (IEC60512)
Contact resistance:	≤10mΩ
Fixing screw torque:	min 0,3; max 0,5 N/m
Temperature range:	-25°C...+80°C
Housing Color:	Black
Protection Class:	IP67
Contact Material:	CuSn gold plated
Mounting:	Anti-vibration system
Overmoulding material:	TPU (Polyurethane)
Coupling nut material:	CuZn nikel plated
O-Ring Material:	FKM (Viton)
Contact holder material:	PA +GF
Conductors Material:	Electrolytic bare copper
Composition:	8 x 0,25
Stranding:	32 x 0,10
Insulation Material:	PVC
Jacket Material:	PUR
Jacket Color:	Black (RAL 9005)



Vista frontale Face view	Chiave/poli Coding/poles	Sistema di bloccaggio Locking system	Collegamenti Connections	Tensione Voltage (V)	Corrente max Max current (A)	Caratteristiche Features	Colore testina Housing color
	A/7-8	Ghiera con antisvitamento Ring nut with anti-vibration system	1) Bianco / White 2) Marrone / Brown 3) Verde / Green 4) Giallo / Yellow 5) Grigio / Grey 6) Rosa / Pink 7) Blu / Blue 8) Rosso / Red	30	2	Senza elettronica Without electronics	Nero Black