

Technical Data



CM8-4P-5MKU





M8 female 90° A-cod. with cable

Made in Italy

PUR 4x0.25 bk 5m







Female



Technical Data

Standard:	IEC 61076-2-104
Rated Voltage:	30 V
Rated Current:	3 A
Insulation:	≥100MΩ (IEC60512)
Contact resistance:	≤10mΩ
Fixing screw torque:	min 0,3; max 0,5 N/m
Temperature range:	-25°C...+80°C
Housing Color:	Black
Protection Class:	IP67
Contact Material:	CuSn gold plated
Mounting:	Anti-vibration system
Overmoulding material:	TPU (Polyurethane)
Coupling nut material:	CuZn nikel plated
O-Ring Material:	FKM (Viton)
Contact holder material:	PA +GF
Conductors Material:	Electrolytic bare copper
Composition:	4 x 0,25
Stranding:	32 x 0,10
Insulation Material:	PVC
Jacket Material:	PUR
Jacket Color:	Black (RAL 9005)

Vista frontale Face view	Chiave/poli Coding/poles	Sistema di bloccaggio Locking system	Collegamenti Connections	Tensione Voltage (V)	Corrente max Max current (A)	Caratteristiche Features	Colore testina Housing color
	A/3	Ghiera con antisvitamento Ring nut with anti-vibration system	1) Marrone / Brown 3) Blu / Blue 4) Nero / Black	60	3	Senza elettronica Without electronics	Nero Black
				30	3	Con elettronica LED With LED electronics 	Trasparente Colorless
	A/4	Ghiera con antisvitamento Ring nut with anti-vibration system	1) Marrone / Brown 2) Bianco / White 3) Blu / Blue 4) Nero / Black	60	3	Senza elettronica Without electronics	Nero Black
				30	3	Con elettronica LED With LED electronics 	Trasparente Colorless