


IZ5052



Inductive sensor

IZB31,2-BPKG/V2A



Product characteristics

Electrical design	PNP
Output function	normally open
Sensing range [mm]	1.2
Housing	cylindrical
Dimensions [mm]	Ø 4 / L = 25

Electrical data

Operating voltage [V]	10...30 DC
Current consumption [mA]	15; (24 V)
Protection class	III
Reverse polarity protection	yes

Outputs

Electrical design	PNP
Output function	normally open
Max. voltage drop switching output DC [V]	2.5
Permanent current rating of switching output DC [mA]	100
Switching frequency DC [Hz]	2000
Short-circuit protection	yes
Type of short-circuit protection	pulsed
Overload protection	yes

Detection zone

Sensing range [mm]	1.2
Operating distance [mm]	0...0.97

Accuracy / deviations

Correction factor	steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminium: 0.4 / copper: 0.3
Hysteresis [% of Sr]	1...15

Operating conditions

Ambient temperature [°C]	-25...70
Protection	IP 65; IP 67

IZ5052



Inductive sensor

IZB31,2-BPKG/V2A

Tests / approvals		
EMC	EN 61000-4-2 ESD	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-6 HF conducted	10 V
	EN 55011	class B
MTTF	[years]	2060


Mechanical data		
Weight	[g]	40
Housing		cylindrical
Mounting		flush mountable
Dimensions	[mm]	Ø 4 / L = 25
Materials		stainless steel (303/1.4305); sensing face: POM

Displays / operating elements		
Display	switching status	1 x LED ring, yellow cable entry lights translucently

Accessories	
Items supplied	Mounting clamps: 1

Remarks	
Pack quantity	1 pcs.

Electrical connection	
Cable: 2 m, PUR; 3 x 0.08 mm²	
Connection	



BN :	brown	
BK:	black	
BU:	blue	
BN	L+	
BK	OUT	DO (NO)
BU	L-	
DO: digital output; NO: normally open		