




1) Sensing surface



Basic features

Application	Object detection
Approval/Conformity	CE UKCA WEEE cULus
Basic standard	IEC 60947-5-2
Principle of operation	Magnetic field sensor
Scope of delivery	Cable clip for C-slot
Trademark	Global

Display/Operation

Function indicator	Active, LED yellow
--------------------	--------------------

Electrical connection

Cable diameter D	2.4 mm
Cable jacket, material	PUR
Cable length L	0.3 m
Connection	M8x1-Male, 3-pin
Polarity reversal protected	yes
Short-circuit protection	yes

Electrical data

Assured switching field strength Ha	2.9 kA/m
Load capacitance max. at Ue	1 µF
No-load current Io max., undamped	2 mA
Operating voltage Ub	10...30 VDC
Output resistance Ra	Open drain
Rated insulation voltage Ui	75 V DC
Rated operating current Ie	100 mA
Rated operating voltage Ue DC	24 V
Rated short circuit current	100 A
Rated switch field strength Hn	2.5 kA/m
Residual current Ir max.	10 µA
Ripple max. (% of Ue)	15 %
Switching frequency	500 Hz
Utilization category	DC -13
Voltage drop static max.	1 V

Environmental conditions

Ambient temperature	-25...85 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 gn, 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
ESD	2A (4 kV)
Emission	Group 1, Class B
IP rating	IP67

Functional safety

MTTF (40 °C)	1879 a
--------------	--------

Interface

Switching output PNP normally open (NO)

Material

Clamping screw material Stainless steel
Housing material PA 12
Material jacket PUR
Material sensing surface PA 12

Mechanical data

Dimension 3.6 x 2.9 x 24 mm
Mounting part Screw M2
Size C-slot
Tightening torque 0.07 Nm

Remarks

Damping magnet axially magnetized
UL-MARKINGS: - For use in NFPA 79 Applications only - Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams (Schematic)

